



A **SHERWIN-WILLIAMS** Company

REF : PAFH 2016 12

Resupatch FH

DESCRIPTION

Resupatch FH is a two-pack easy to use fast-cure epoxy resin mortar, with excellent mechanical properties. This makes it ideal for rapid repair of concrete surfaces in heavy duty environments.

Resupatch FH is a fast-cure mortar for same day repairs which can be overlaid in 4 hours at 20°C.

ADVANTAGES

- Fast cure & low odour
- Hard wearing durable repairs for Industrial Use
- Ease of application
- Minimum surface preparation
- Can be feather edged
- Excellent abrasion and impact resistance
- Concrete like in appearance
- Dust-free & permanent

RECOMMENDED USES

- Any sound concrete requiring repairs
- Warehouse areas
- Chemical production and Storage
- Printing and packaging Areas
- Engineering facilities
- Automotive industry
- Aerospace production areas
- Industrial workshops

PRODUCT INFORMATION

System thickness (dry)	Solids content	Pack sizes	Pack make up	Shelf life	Storage
As Required	100%	5 kg. & 20 kg.	5 kg. unit - 1 X Base/Aggregate Blend 1 X Hardener 20 kg. unit- 1 X Base/Aggregate Blend 1 X Hardener	12 Months (Base & Hardener) 3 Months (Aggregate)	Keep out of direct Sunlight Store in a Dry Place

DRYING TIMES & COVERAGE RATES at 20 ° C

Coverage rate	Pot life	Recoat time	Light traffic	Full traffic	Full chemical cure
5 kg. has a 2.2 Litre volume 20 kg. has a 9 Litre volume	Including Aggregate (15 Mins)	For Seal Coats 4 Hours	8 Hours	24 - 36 Hours	Up to 7 Days



